


Pump and Automation Valves

Drainage




Ama-Dainer N	
Rp	1¼ - 1½
Q [m3/h]	max. 16.5
H [m]	max. 12
T [°C]	max. +50 (301, 302, 303) max. +35 (358)




Ama-Drainer 400/500	
Rp	1½ - 2
Q [m3/h]	max. 50
H [m]	max. 24
T [°C]	max. +40



Ama-Drainer 80, 100	
Rp	2½ / 100
Q [m3/h]	max. 130
H [m]	max. 26
T [°C]	max. +50




Amarex N	
DN	50 - 100
Q [m3/h]	max. 190
H [m]	max. 49
T [°C]	max. +60



Amarex KRT	
DN	40 - 700
Q [m3/h]	max. 10080
H [m]	max. 120
T [°C]	max. +60
n [min ⁻¹]	max. 2900




Compacta	
DN	80 - 100
Q [m3/h]	max. 140
H [m]	max. 24
T [°C]	max. +40 up to +65 for short periods




Etabloc PumpDrive	
DN	25 - 150
Q [m3/h]	max. 660
H [m]	max. 101
T [°C]	max. +110
p [bar]	max. 16
n [min ⁻¹]	max. 4200

*Applicable in HVAC as well



Etachrom BC PumpDrive	
DN	25 - 80
Q [m3/h]	max. 260
H [m]	max. 106
T [°C]	max. +110
p [bar]	max. 12
n [min ⁻¹]	max. 3600


*Applicable in HVAC as well




Etanorm PumpDrive	
DN	25 - 150
Q [m3/h]	max. 660
H [m]	max. 160
T [°C]	max. +140
p [bar]	max. 16
n [min ⁻¹]	max. 4200

*Applicable in HVAC as well


Water Supply / Fire Fighting



Multitec	
DN	32 - 150
Q [m3/h]	max. 850
H [m]	max. 630 (1000)
T [°C]	max. +200
p [bar]	max. 63 (100)
n [min ⁻¹]	max. 4000




FFS	
DN	32 - 300
Q [m3/h]	max. 840
H [m]	max. 140
T [°C]	+5 to +50
p [bar]	max. 16
n [min ⁻¹]	max. 3000




FFU	
DN	32 - 350
Q [m3/h]	max. 2500
H [m]	max. 150
T [°C]	+5 to +50
p [bar]	max. 25
n [min ⁻¹]	max. 3000




Omega	
DN	80 - 350
Q [m3/h]	max. 2880
H [m]	max. 210
T [°C]	max. +80 / max. 140
p [bar]	max. 25
n [min ⁻¹]	max. 4000




Moviboost	
Rp / DN	1½ / 250
Q [m3/h]	max. 450
H [m]	max. 150
T [°C]	max. +70
p [bar]	max. 16




Hya-Solo D/DV	
Rp/DN	1¼ / 100
Q [m3/h]	max. 110
H [m]	max. 150
T [°C]	max. +70
p [bar]	max. 16



UPA 100C	
DN	100
Q [m3/h]	max. 16
H [m]	max. 400
T [°C]	max. +30



Movitec PumpDrive	
DN	25 - 100
Q [m3/h]	max. 113
H [m]	max. 401
T [°C]	max. +140
p [bar]	max. 40
n [min ⁻¹]	max. 2900




Etanorm SYT	
DN	32 - 300
Q [m3/h]	max. 1900
H [m]	max. 102
T [°C]	max. +350
p [bar]	max. 16


HVAC




Calio	
Rp/DN	1 - 1¼ / 32 - 100
Q [m3/h]	max. 70
H [m]	max. 18
T [°C]	-10 to +110
p [bar]	max. 16
n [min ⁻¹]	max. 3660




RioTherm	
Rp	1 - 1¼
Q [m3/h]	max. 10
H [m]	max. 6
T [°C]	-2 to +110
p [bar]	max. 10



Etaline PumpDrive	
DN	32 - 200
Q [m3/h]	max. 788
H [m]	max. 100
T [°C]	-10 to +140
p [bar]	max. 16
n [min ⁻¹]	max. 4200



BOA-H	
<i>Globe Valve</i>	
PN	16
DN	20 - 300
T [°C]	-10 to +300




BOA-S	
<i>Strainer</i>	
PN	6 / 16 / 25
DN	15 - 300
T [°C]	-10 to +350



BOA-Compact	
<i>Globe Valve</i>	
PN	6 / 16
DN	15 - 200
T [°C]	-10 to +120




SISTO-16RGA	
<i>Diaphragm Valve</i>	
PN	16
DN	15 - 80
T [°C]	-10 to +90
NPS	1/2" - 3"




BOA-SuperCompact	
<i>Globe Valve</i>	
PN	6 / 10 / 16
DN	20 - 200
T [°C]	-10 to +120




Ecoline BLT 150 - 300	
<i>Ball Valve</i>	
Class	150 / 300
DN	½" - 12"
T [°C]	15 - 300
T [°C]	-10 to +200




BOA-H Mat E	
<i>Control and Balancing Valve</i>	
PN	16 / 25
DN	20 - 150
T [°C]	-10 to +350




Ecoline GTR	
<i>Gate Valve</i>	
PN	10 / 16
DN	40 - 600
T [°C]	max. 70°C




BOA-RVK	
<i>Non-return Valve</i>	
PN	6 / 10 / 16
DN	15 - 200
T [°C]	-30 to +250



BOAX-B	
<i>Butterfly Valve</i>	
PN	10 / 16
DN	40 - 1000
T [°C]	-10 to +110




SEIRE 2000	
<i>Swing Check Valve</i>	
PN	max. 25
DN	50 - 600
T [°C]	-18 to +343




HEAD-BD	
PN	max. 10 bar
DN	50 - 1200
T [°C]	-10 to +120

Other KSB Products



SuPremE Motor	
No. of Pump	max. 1
Voltage [V]	
Power supply via PumpDrive variable speed system only	



PumpMeter	
No. of Pump	max. 1
Type	See pump type series
Installation	Factory-mounted, IP65
Voltage	24 V DC